
































	Order No.	Description
	9190	<b>Hydraulic tubing.</b> 3/8" O.D. x .065" wall, 15,3 m. (10 pieces 1,53 m long.) Wt. 5,5 kg.
	9670	<b>Tee adapter.</b> For installing gauge between pump and hose coupling. Has 1/4" and 3/8" NPTF female and 3/8" NPTF male ports. Wt. 0,2 kg.
	9671	<b>Double tee adapter.</b> Permits use of more than one cylinder in series with one pump. Three 3/8" NPTF female ports. Wt. 0,5 kg.
	9672	<b>Service tee.</b> Two 3/8" NPTF female internal, one 3/8" NPTF male external. Wt. 0,3 kg.
	9673*	<b>Swivel connector.</b> 3/8" NPSM male, 1/4" NPSM female. Wt. 0,1 kg.
	9674	<b>Male connector.</b> 43 mm long, 1/4" x 3/8" NPTF. Wt. 0,1 kg.
	9675*	<b>Swivel connector.</b> 3/8" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.
	9676*	<b>Swivel connector.</b> 1/4" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.
	9677*	<b>45° swivel connector.</b> 3/8" NPTF male, 3/8" NPSM female. Wt. 0,1 kg.
	9678	<b>45° fitting.</b> Used when mounting gauge at an angle on connection such as 9670. Male and female 1/4" NPTF ends. Wt. 0,1 kg.
	9679	<b>Connector.</b> 1/4" NPTF female and 3/8" NPTF male. Wt. 0,1 kg.
	9680	<b>Coupling.</b> Both ends 3/8" NPTF female. Wt. 0,1 kg.
	9681	<b>Street elbow.</b> Male and female 3/8" NPTF ends. Wt. 0,1 kg.
	9682	<b>Male connector.</b> 43 mm long, 3/8" NPTF male ends. Wt. 0,1 kg.
	9683	<b>Male connector.</b> 57 mm long, 3/8" NPTF male ends. Wt. 0,1 kg.

	Order No.	Description
	9684	<b>Male connector.</b> 57 mm long, 1/4" NPTF male ends. Wt. 0,1 kg.
	9685	<b>Coupling.</b> 1/4" NPTF female and 3/8" NPTF female. Wt. 0,1 kg.
	9686	<b>90° elbow.</b> 3/8" NPTF female ends. Wt. 0,2 kg.
	9687	<b>Pipe plug.</b> Heat-treated, 3/8" NPTF. Wt. 0,1 kg.
	9688	<b>Pipe plug.</b> Heat-treated, 1/4" NPTF. Wt. 0,1 kg.
	9689	<b>Connector.</b> 1/4" NPTF male and 3/8" NPTF female. Wt. 0,1 kg.
	9690	<b>Male connector.</b> 43 mm long, 1/4" NPTF male ends. Wt. 0,1 kg.
	9692	<b>Straight connector.</b> 3/8" tube x 3/8" male NPTF. Wt. 0,1 kg.
	9693	<b>90° elbow.</b> 3/8" tube x 3/8" male NPTF. Wt. 0,1 kg.
	9694	<b>45° elbow.</b> 3/8" tube x 1/4" male NPTF. Wt. 0,1 kg.
	9695	<b>Tee.</b> 3/8" tube. Wt. 0,1 kg.
	9696	<b>Male run tee.</b> 3/8" tube x 1/4" male NPTF. Wt. 0,1 kg.
	9697	<b>Male branch tee.</b> 3/8" tube x 1/4" male NPTF. Wt. 0,1 kg.
	9698	<b>Cross.</b> 3/8" tube. Wt. 0,2 kg.
	9699	<b>45° gauge fitting.</b> 3/8" NPTF male and female, and 1/4" NPTF female at 45°. Wt. 0,3 kg.
	9705	<b>Fitting, swivel.</b> 3/8" NPTF male to 3/8" NPTF female. 90° fitting with internal 370 micron screen. May be rotated 360° about male thread axis.

\* **CAUTION:** On part numbers 9673, 9675, 9676 and 9677 the female swivel end of these adapters is a straight pipe thread (NPSM) with a 30° seat. All male pipe fittings that are used with these female swivel adapters must have an internal 30° seat in order to effect a proper seal. All Power Team male fittings are manufactured with a 30° seat except 9687 and 9688.

**NOTE:** Power Team hydraulic fittings are intended for use with our high pressure hydraulic products and are suitable for use at max. working pressures of 700 Bar unless otherwise noted.